

1 1

## NOTICE INVITING QUOTATION

Sealed item rate quotations are invited for "Replacement of damaged kota stone flooring in Boys Hostel-II in MANUU Campus, Gachibowli, Hyderabad" to reach the office of the I/c Engineering Section, Room No.16 Ground floor, Admin Building MANUU Gachibowli, Hyderabad.

Notice Inviting Quotation No.	MANUU/ENGG/2025-26/F514/ date 4-07-2025		
Type of Tender/Form of Contract/ Bidding	Open/ Works Contract/		
Name of Work	For Replacement of damaged kota stone flooring in Boys Hostel-II in MANUU Campus, Gachibowli, Hyderabad		
Estimated Amount	Rs 1,34,600/-		
Earnest Money Deposit (EMD)	Rs 3,000/- ( i.e. 2% of the estimated amount (DD/Bank Guarantee in favour of Finance Officer, MANUU payable at Hyderabad)		
Performance Guarantee	5% of the Contract value (DD/Bank Guarantee in favour of Finance Officer, MANUU payable at Hyderabad)		
Date of start of Bid Submission	J 4 -07-2025 @ 11:00 AM		
Last date & Time for submission of Bids	<b>22</b> -07-2025 @ 11:00 AM		

1

Blank quotation form can be downloaded from the MANUU website.

dun Engineering Section

MANUU

	Campus, Gachibowli, Hyderabad		oys Host		n MANU
	MANUU/ENGG/2025-26/F51%/				
	Description	Otv	Unit	Rate	Amour
manufactured sand derived from Recycled Concrete Aggregate (RCA) upto 25% : 4 graded stone aggregate 20 mm nominal size including Recycled Concrete Aggregate (RCA) upto 25%)			Cum		
lead as per					
Nominal concrete 1:3:6 or richer mix (i/c equivalent design mix)			Cum		
trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift upto 1.5 m.			Cum		•
conforming the manuf shades exc as approve steps and c 1:3 (1 cen cement show white ceme complete	g to 1S: 15622 (thickness to be specified by acturer), of approved make, in all colours, ept burgundy, bottle green, black of any size d by Engineer-in-Charge, in skirting, risers of ados, over 12 mm thick bed of cement mortar nent : 3coarse sand) and jointing with grey arry @ 3.3kg per sqm.including pointing in ent mixed with pigment of matching shade	2.5	Sam		
with pigme rubbing an	ent to match the shade of the slab including d polishing complete with base of cement	-			
25 mm thic	k	45	Sam		
Dismantling mortar incl lead.	g tile work in floors and roofs laid in cement uding stacking material within 50 metres				
For thickne	ss of tiles above 25 mm and up to 40 mm	46	Sqm		
		ŀ	Amount ir	n Rs:	
		Т	The second s		
nt in words)					
	manufactu Aggregate 20 mm no Aggregate Demolishi means inc lead as per Nominal c design mix Filling av trenches, I exceeding layer by ra upto 1.5 m Providing conforming the manuf shades exc as approve steps and d 1:3 (1 cen cement slu white ceme complete Kota Stone base laid ov with pigme rubbing an mortar 1: 4 25 mm thic Dismantling mortar incl lead.	<ul> <li>1:2:4 (1 cement : 2 coarse sand (zone-III) including manufactured sand derived from Recycled Concrete Aggregate (RCA) upto 25% : 4 graded stone aggregate 20 mm nominal size including Recycled Concrete Aggregate (RCA) upto 25%)</li> <li>Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.</li> <li>Nominal concrete 1:3:6 or richer mix (i/c equivalent design mix)</li> <li>Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift upto 1.5 m.</li> <li>Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm.including pointing in white cement mixed with pigment of matching shade complete</li> <li>Kota Stone slab flooring over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab including rubbing and polishing complete with base of cement mortar 1:4 (1 cement :4 coarse sand):</li> <li>25 mm thick</li> <li>Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.</li> <li>For thickness of tiles above 25 mm and up to 40 mm</li> </ul>	1:2:4 (1 cement : 2 coarse sand (zone-III) including manufactured sand derived from Recycled Concrete Aggregate (RCA) upto 25% : 4 graded stone aggregate 20 mm nominal size including Recycled Concrete Aggregate (RCA) upto 25%)       4         Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.       3         Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift upto 1.5 m.       3         Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm.including pointing in white cement mixed with pigment of matching shade complete       2.5         Kota Stone slab flooring over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab including rubbing and polishing complete with base of cement mortar 1: 4 (1 cement :4 coarse sand) :       45         Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.       45         Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead	1:2:4 (1 cement : 2 coarse sand (zone-III) including manufactured sand derived from Recycled Concrete Aggregate (RCA) upto 25% : 4 graded stone aggregate 20 mm nominal size including Recycled Concrete Aggregate (RCA) upto 25%)       4       Cum         Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.       3       Cum         Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift upto 1.5 m.       3       Cum         Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3coarse sand) and jointing with grey cement slurry (a 3.3kg per sym.including pointing in white cement mixed with pigment of matching shade complete       2.5       Sqm         Kota Stone slab flooring over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab including rubbing and polishing complete with base of cement mortar including stacking material within 50 metres lead.       45       Sqm         For thickness of tiles above 25 mm and up to 40 mm       46       Sqm         Amount in mut in words)       Amount in Contal Amo	1:2:4 (1 cement : 2 coarse sand (zone-III) including manufactured sand derived from Recycled Concrete Aggregate (RCA) upto 25% : 4 graded stone aggregate 20 mm nominal size including Recycled Concrete Aggregate (RCA) upto 25%)       4       Cum         Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.       3       Cum         Nominal concrete 1:3:6 or richer mix (i/c equivalent design mix)       3       Cum         Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift upto 1.5 m.       3       Cum         Providing and fixing 1st quality ceramic glazed wall tiles conforming to 1S: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slury @ 3.3kg per sqm.including pointing in white cement mixed with pigment of matching shade complete Kota Stone slab flooring over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab including rubbing and polishing complete with base of cement mortar 1:4 (1 cement :4 coarse sand) : 25 mm thick       45       Sqm         Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.       46       Sqm         For thickness of tiles above 25 m

Signature of Contractor

## Details of the Contractor

S.No.	Particulars	To be filled by the Contractor
1	Name of the Firm	
2	Name of the Contractor	
3	Contractor Address	
(a)	Mobile	
(b)	E-Mail Id	
4	Name of the Bank	
5	Name of the Branch	
6	Account No.(prefix with zeros, if any as given on the cheque book/passbook)	
7	IFSC Code of the Branch	
8	MICR Code	
9	PAN No.	
10	GST No.	
11	State whether Terms & Conditions mentioned in the Quotation are accepted ? Yes/No	
12	Is EMD submitte/attached ? Yes/No	

I/we undertake and confirm that our firm/partnership firm has not been blacklisted by any state/Central Departments/PSUs/Autonomous bodies during its operations. Further, if such information comes to the notice of the University then I/we shall be liable for appropriate action as per the provisions laid down by the University or Govt. of India.

Signature of Contractor

## Terms and Conditions

- 1. The work should be carried out strictly as per the specification and as per the directions of Engineer-incharge.
- 2. Safety measures as specified in CPWD general conditions of contract should be adopted to protect the labour from every risk specifically while executing the work.
- 3. Before tendering, the contractor shall inspect site of work on all working days from 09:00 AM to 05:00 PM and shall fully acquaint himself about the conditions prevailing at site, availability of materials in market, availability of ready site and suitable locations for execution of the work involved in achieving the completion of work.
- 4. The contractor shall at his own expense and risk arrange the storage of materials at site of the work for carrying out of all jobs connected with the completion of the work. The contractor shall have to abide by the regulations of the authorities concerned and the directions of the I/c Engineering Section. If during construction, it becomes necessary to remove or shift the equipment, material, etc, to facilitate execution, the contractor shall carry out the removal of shifting as directed by the I/c Engineering Section and re-shift to its original position and no claim whatsoever, shall be entertained on this account.
- 5. It shall be deemed that the contractor has satisfied himself as to the nature and location of the work, transport facilities, availability of site, etc. the department will bear no responsibility for lack of such knowledge & the consequences thereof.
- 6. The I/c Engineering Section shall have full powers for removal of any or all of the materials brought to site by contractor which are not in accordance with the contract specifications or do not conform, in character or quality. In case of default on the part of the contractor in removing rejected materials, the I/c Engineering Section shall be at liberty to have them removed at the risk and cost of the contractor.
- 7. The work shall be carried out in such a manner so as not to interfere / or adversely / or disturb the functioning of the University and other works being executed by other agencies, if any.
- 8. Any damage done by the contractor to any existing work or work being executed by other agencies shall be made good by him at his own cost.
- 9. The contractor shall maintain in good condition all work executed till the completion of entire work entrusted to the contract under this contract.
- 10. No payment shall be made to the contractor for damage caused by rain, flood and other natural calamities whatsoever during the execution of works and any damage to the work on this account shall have to be made good by the contractor at his own cost.
- 11. The Contractor shall take instructions from the I/c Engineering Section regarding collections and stacking of materials at site.
- 12. The Contractor shall be responsible to arrange at his own cost all necessary tools and tackles required for execution of the works including incidental original and maintenance works.
- 13. The operating cost of contractor's machinery at site i.e. Coolants/ lubricants/ Petrol/ Kerosene Oil/ Mobile Oil/ etc, if any shall be borne by the contractor himself.
- 14. The University shall not be responsible for any injury partial or permanent or death of any workers at site due to accident or malfunctioning of the equipment or by negligence of the Contractors staff on site.
- 15. If any damage caused for public conveniences/ services, the same shall have to be repaired instant, failing which necessary recovery shall be make from the bill.
- 16. If any Building, Road and Channels damaged by the Contractor the same shall have to be repair by the Contractor at his risk and cost, otherwise the complete cost will be recovered as intimated by the I/c Engineering Section.

- 17. The rate quoted by the contractor shall include all incidental expenses if nay.
- 18. No extra payment what so ever shall be paid to the contractor other than the quoted price.
- 19. Verbal quotation or incomplete quotation will be rejected.
- 20. Any variation in the specification(s) during repair/servicing will be rejected.
- 21. Time allowed is.....days and starts from the date of issue of Work Order. In case of delay in completion of the contract, Liquidate damages (LD) at one percent of the contract value per week of delay subject to a maximum of ten percent of contract value shall be levied.
- 22. The work shall be carried out to the entire satisfaction of the I/c Engineering Section.
- 23. Payment shall be made on submission of Invoice after satisfactory execution of the work and as per actual measurements
- 24. The tax as applicable shall be deducted from the gross amount of the bill.
- 25. The performance security will be forfeited and credited to the MANUU account in the event of a breach of contract by the contractor. However it shall be refunded to the contractor without interest after duly performs and complete all obligations.
- 26. The Security Deposit @ 2.5 percent on contract value shall be deducted and shall be refund on completion of Defect Liability Period.

c Engineering Section

-000-