



NOTICE INVITING QUOTATION

Sealed item rate quotations are invited for “Rectification of Seepage in ITI building in MANUU Campus, Gachibowli, Hyderabad” to reach the office of the I/c Engineering Section, Room No.16 Ground floor, Admin Building MANUU Gachibowli, Hyderabad.

Notice Inviting Quotation No. 17	MANUU/ENGG/2025-26/F248/ date 28 -08-2025
Type of Tender/Form of Contract/ Bidding	Open/ Works Contract/
Name of Work	For Rectification of Seepage in ITI building in MANUU Campus, Gachibowli, Hyderabad
Estimated Amount	Rs 2,60,000/-
Earnest Money Deposit (EMD)	Rs 5,200/- (i.e. 2% of the estimated amount (DD/Bank Guarantee in favour of Finance Officer, MANUU payable at Hyderabad)
Performance Guarantee	5% of the Contract value (DD/Bank Guarantee in favour of Finance Officer, MANUU payable at Hyderabad)
Date of start of Bid Submission	28 -08-2025 @ 11:00 AM
Last date & Time for submission of Bids	10 -09-2025 @ 11:00 AM

Blank quotation form can be downloaded from the MANUU website.

I/c Engineering Section
MANUU

SCHEDULE OF QUANTITIES

Name of Work:		Rectification of Seepage in ITI building in MANUU Campus, Gachibowli, Hyderabad			
No:		MANUU/ENGG/2025-26/F248/ 17			
DSR No	Description	Unit	Rate	Qty	Amount
15.23	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.				
15.23.1	For thickness of tiles 10 mm to 25 mm	Sqm	18.0		
15.2	Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.				
15.2.1	Nominal concrete 1:3:6 or richer mix (i/c equivalent design mix)	Cum	8		
6.13	Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level.				
6.13.1	Cement mortar 1:3 (1 cement :3 coarse sand)	Sqm	2.40		
4.2	Providing and laying cement concrete in retaining walls, return walls, walls (any thickness) including attached pilasters, columns, piers, abutments, pillars, posts, struts, buttresses, string or lacing courses, parapets, coping, bed blocks, anchor blocks, plain window sills, fillets, sunken floor etc., up to floor five level, excluding the cost of centering, shuttering and finishing:				
4.2.3A	1:2:4 (1 Cement : 2 coarse sand (zone-III) including manufactured sand derived from Recycled Concrete Aggregate (RCA) upto 25% : 4 graded stone aggregate 20 mm nominal size Recycled Concrete Aggregate (RCA) upto 25%).	Cum	7.50		
4.2.8A	1:5:10 (1 cement : 5 manufactured sand derived from Recycled Concrete Aggregate (RCA) : 10 graded stone aggregate 40mm nominal size Recycled Aggregate (RA))	Cum	2.50		
11.39	Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to IS : 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete.	sqm	18.00		
14.75	Repair to plaster of thickness 12mm to 20 mm in patches of area 2.5sqm and under, including cutting the patch in proper shape, raking out joints and preparing plastering the wall surface with white cement based polymer modified self curing mortar, including disposal of rubbish, all complete as per the direction of Engineer-In-Charge.	Sqm	15.0		

DSR No	Description	Unit	Rate	Qty	Amount
17.2	Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required :				
17.2.1	W.C. pan with ISI marked white solid plastic seat and lid	No.	2.0		
17.1	Providing and fixing water closet squatting pan (Indian type W.C.pan) with 100 mm sand cast Iron P or S trap, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever) conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required:				
17.1.1	White Vitreous china Orissa pattern W.C. pan of size 580x440 mm with integral type foot rests	No.	2.0		
NSR-1	Providing and fixing at all floors Type-B SWR PVC pipes including all fittings such as plain and door bends,tees,elbows,equal and unequal junctions,heel rest sanitary bends,collars etc.(except floor traps/p traps) confirming to IS 13592,IS 14735 including jointing with solvent and providing necessary supports,clamps/MS brackets at special jointing in exposed areas like in shafts etc. and pasted type(solvent) for all other locations all complete and as per the directions of Engineer-in-charge. MS brackets shall ve paid separately				
NSR-1.1	110mm diameter	metre	16		
NSR-1.2	75mm diameter	metre	16		
15.60	Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading,transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.	Cum	10		
13.80	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	Sqm	40		
13.82	Wall painting with acrylic emulsion paint, having VOC (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour.				
13.82.2	Two coats.	Sqm	160		

DSR No	Description	Unit	Qty	Rate	Amount
22.5	<p>Providing and laying water proofing treatment in sunken portion of WCs, bathroom etc., by applying cement slurry mixed with water proofing cement compound consisting of applying :</p> <p>(a) First layer of slurry of cement @ 0.488 kg/sqm mixed with water proofing cement compound @ 0.253 kg/ sqm. This layer will be allowed to air cure for 4 hours (b) Second layer of slurry of cement @ 0.242 kg/sqm mixed with water proofing cement compound @ 0.126 kg/sqm. This layer will be allowed to air cure for 4 hours followed with water curing for 48 hours.</p> <p>The rate includes preparation of surface, treatment and sealing of all joints, corners, junctions of pipes and masonry with polymer mixed slurry.</p>	sqm	22		
15.60	Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.	Cum	10		
21.1	<p>Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :</p>				
21.1.1	For fixed portion				
21.1.1.2	Powder coated aluminium (minimum thickness of powder coating 50 micron)	Kg	20		
21.1.2	For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately).				
21.1.2.2	Powder coated aluminium (minimum thickness of powder coating 50 micron)	Kg	15		

DSR No	Description	Unit	Qty	Rate	Amount
21.3	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item):				
21.3.2	With float glass panes of 5 mm thickness (weight not less than 12.50 kg/sqm)	Sqm	4		
21.3.3	With float glass panes of 8 mm thickness (weight not less than 20 kg/sqm)	Sqm	4		
21.8	Filling the gap in between aluminium frame & adjacent RCC/ Brick/ Stone work by providing weather silicon sealant over backer rod of approved quality as per architectural drawings and direction of Engineer-in-charge complete.				
21.8.1	Upto 5mm depth and 5 mm width	m	6		
21.13	Providing and fixing Brass 100mm mortice latch and lock with 6 levers without pair of handles (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.	No.	1		
9.83	Providing and fixing aluminium die cast body tubular type universal hydraulic door closer (having brand logo with ISI, IS : 3564, embossed on the body, door weight upto 35 kg and door width upto 700 mm), with necessary accessories and screws etc. complete.	No.	1		
9.97	Providing and fixing aluminium tower bolts ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with necessary screws etc. complete :				
9.97.1	300x10 mm	No.	2		
9.100	Providing and fixing aluminium handles ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with necessary screws etc. complete :				
9.100.1	125 mm	No.	4		
Amount in Rs:					
GST :					
Total Amount(incl GST):					
(Total amount in words) _____					
				Sd/- I/c Engineering Section	

Signature of Contractor

Details of the Contractor

S.No.	Particulars	To be filled by the Contractor
1	Name of the Firm	
2	Name of the Contractor	
3	Contractor Address	
(a)	Mobile	
(b)	E-Mail Id	
4	Name of the Bank	
5	Name of the Branch	
6	Account No.(prefix with zeros, if any as given on the cheque book/passbook)	
7	IFSC Code of the Branch	
8	MICR Code	
9	PAN No.	
10	GST No.	
11	State whether Terms & Conditions mentioned in the Quotation are accepted ? Yes/No	
12	Is EMD submitte/attached ? Yes/No	

I/we undertake and confirm that our firm/partnership firm has not been blacklisted by any state/Central Departments/PSUs/Autonomous bodies during its operations. Further, if such information comes to the notice of the University then I/we shall be liable for appropriate action as per the provisions laid down by the University or Govt. of India.

Signature of Contractor

Terms and Conditions

1. The work should be carried out strictly as per the specification and as per the directions of Engineer-in-charge.
2. Safety measures as specified in CPWD general conditions of contract should be adopted to protect the labour from every risk specifically while executing the work.
3. Before tendering, the contractor shall inspect site of work on all working days from 09:00 AM to 05:00 PM and shall fully acquaint himself about the conditions prevailing at site, availability of materials in market, availability of ready site and suitable locations for execution of the work involved in achieving the completion of work.
4. The contractor shall at his own expense and risk arrange the storage of materials at site of the work for carrying out of all jobs connected with the completion of the work. The contractor shall have to abide by the regulations of the authorities concerned and the directions of the I/c Engineering Section. If during construction, it becomes necessary to remove or shift the equipment, material, etc, to facilitate execution, the contractor shall carry out the removal of shifting as directed by the I/c Engineering Section and re-shift to its original position and no claim whatsoever, shall be entertained on this account.
5. It shall be deemed that the contractor has satisfied himself as to the nature and location of the work, transport facilities, availability of site, etc. the department will bear no responsibility for lack of such knowledge & the consequences thereof.
6. The I/c Engineering Section shall have full powers for removal of any or all of the materials brought to site by contractor which are not in accordance with the contract specifications or do not conform, in character or quality. In case of default on the part of the contractor in removing rejected materials, the I/c Engineering Section shall be at liberty to have them removed at the risk and cost of the contractor.
7. The work shall be carried out in such a manner so as not to interfere / or adversely / or disturb the functioning of the University and other works being executed by other agencies, if any.
8. Any damage done by the contractor to any existing work or work being executed by other agencies shall be made good by him at his own cost.
9. The contractor shall maintain in good condition all work executed till the completion of entire work entrusted to the contract under this contract.
10. No payment shall be made to the contractor for damage caused by rain, flood and other natural calamities whatsoever during the execution of works and any damage to the work on this account shall have to be made good by the contractor at his own cost.
11. The Contractor shall take instructions from the I/c Engineering Section regarding collections and stacking of materials at site.
12. The Contractor shall be responsible to arrange at his own cost all necessary tools and tackles required for execution of the works including incidental original and maintenance works.
13. The operating cost of contractor's machinery at site i.e. Coolants/ lubricants/ Petrol/ Kerosene Oil/ Mobile Oil/ etc, if any shall be borne by the contractor himself.
14. The University shall not be responsible for any injury partial or permanent or death of any workers at site due to accident or malfunctioning of the equipment or by negligence of the Contractors staff on site.
15. If any damage caused for public conveniences/ services, the same shall have to be repaired instant, failing which necessary recovery shall be make from the bill.
16. If any Building, Road and Channels damaged by the Contractor the same shall have to be repair by the Contractor at his risk and cost, otherwise the complete cost will be recovered as intimated by the I/c Engineering Section.

17. The rate quoted by the contractor shall include all incidental expenses if nay.
18. No extra payment what so ever shall be paid to the contractor other than the quoted price.
19. Verbal quotation or incomplete quotation will be rejected.
20. Any variation in the specification(s) during repair/servicing will be rejected.
21. Time allowed is 30 days and starts from the date of issue of Work Order. In case of delay in completion of the contract, Liquidate damages (LD) at one percent of the contract value per week of delay subject to a maximum of ten percent of contract value shall be levied.
22. The work shall be carried out to the entire satisfaction of the I/c Engineering Section.
23. Payment shall be made on submission of Invoice after satisfactory execution of the work and as per actual measurements
24. The tax as applicable shall be deducted from the gross amount of the bill.
25. The performance security will be forfeited and credited to the MANUU account in the event of a breach of contract by the contractor. However it shall be refunded to the contractor without interest after duly performs and complete all obligations.
26. The Security Deposit @ 2.5 percent on contract value shall be deducted and shall be refund on completion of Defect Liability Period.


28/08/15
I/c Engineering Section

-000-